



## LT XLPE CABLE

TDS Doc.No:PIL/TE/250425/002786

DESIGN CODE : LVIS09AXSWYF004C2.5SA001S

Particulars	4 Core X 2.5 Sq.mm
Name of Manufacturer	Polycab India Ltd
Type of cable	A2XWY
Voltage Grade V	1100
No of cores X size in sqmm	4 Core X 2.5 Sq.mm
Conductor	
a) Material	H2/H4 Grade Aluminium as per Class 1 of IS: 8130/2013, latest
b) Max. d.c. resistance of conductor at 20° C (ohm/km)	12.100
c) Shape of the conductor	Solid Circular
Insulation	
a) Material	XLPE as per IS 7098(Pt-1)/88, Latest
b) Nominal thickness (mm)	0.7
c) Core identification	Red, Yellow, Blue, Black
Inner Sheath	
a) Material	Extruded PVC Type ST2 as per IS:5831/84
b) Minimum thickness (mm)	0.3
Armouring	
a) Material	Galvanised Steel
b) Type of armouring	Round Wire
c) Nominal size of armour (mm)	1.4
d) Tolerance on armour dimensions	± 0.040 mm
Outer Sheath	
a) Material	Extruded FR PVC Type 'ST2' as per IS:5831/84
b) Thickness (mm)	1.24 (Min.)
c) Colour of sheath	Black
Electrical Parameters	
a) Max. a.c. resistance of conductor at 90° C (ohm/km)	15.5
b) Calculated Cable reactance (ohm/km)	0.0981

c) Impedance of cable (ohm/km)	15.5
d) Approx. Cable Capacitance (mfd/km)	0.19
Maximum conductor temperature under normal operating conditions	90°C
Maximum conductor temperature at the termination of short circuit	250°C
Short Circuit rating of conductor for the duration of 1 sec (kA)	0.24
<b>Continuous Current carrying capacities :-</b>	
(a) In Ground at 30°C (A)	27
(b) In Air at 40°C (A)	24
Applicable Standard	IS 7098 Part I/88, IS 8130/2013, IS 5831/84, IS 3975/1999 etc. with latest up to date amendments
Approx. overall diameter of the cable in mm	14.5 ± 2.0
Minimum bending radius	12 times Overall diameter
Max. Tensile strength	
(i) for Cables pulled with stocking (Newtons)	9 x D <sup>2</sup> , D is the cable OD in mm
(ii) for Cables pulled with pulling eyes (N)	300
Embossing	POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE FR
Printing	YEAR POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE FR CABLE SIZE CABLE TYPE WITH SEQUENTIAL MARKING at every one meter interval.
Standard Drum Length (Mtr.)	1000 Mtr. ±5%
Non- Standard Drum Length (Mtr.)	Maximum 5% of order quantity and Min Individual Non-Standard Drum 200 meters
<b>FR PROPERTIES</b>	
a) Oxygen Index	Min. 29% as per ASTM D- 2863
b) Temperature Index	Min. 250 Deg.C as per ASTM D- 2863
e) Flammability Test	As per IEC:332-I