




LT XLPE CABLE

TDS Doc.No:PIL/TE/250425/002768

DESIGN CODE : LVIS09CXUAY2061C1.5SA001S

Particulars		61 Core X 1.5 Sq.mm
Name of Manufacturer		Polycab India Ltd.
Type of cable		2XY
Voltage Grade V		1100
No of cores X size in sqmm		61 Core X 1.5 Sq.mm
Conductor		
a)	Material	Plain annealed Copper as per Class 1 of IS:8130/2013
b)	Max. d.c. resistance of conductor at 20° C (ohm/km)	12.10
c)	Shape of the conductor	Solid Circular
Insulation		
a)	Material	XLPE as per IS 7098(Pt-1)/88, Latest
b)	Nominal thickness (mm)	0.7
c)	Core Identification	All cores Grey with number printing
Inner Sheath		
a)	Material	Extruded PVC Type ST2 as per IS:5831/84
b)	Minimum thickness (mm)	0.4
Armouring		Not Applicable
Outer Sheath		
a)	Material	Extruded PVC Type ST2 as per IS:5831/84
b)	Thickness (mm)	2.2 (Nom.)
c)	Colour of outer sheath.	Black
Electrical Parameters		
a)	Max. a.c. resistance of conductor at 90° C (ohm/km)	15.4
b)	Calculated Cable reactance (ohm/km)	0.106
c)	Impedance of cable (ohm/km)	15.4
Maximum conductor temperature under normal operating conditions		90°C
Maximum conductor temperature at the termination of short circuit		250°C

Short Circuit rating of conductor for the duration of 1 sec (kA) 0.21

Continuous Current carrying capacities :-

(a) In Ground at 30°C (A) 9

(b) In Air at 40°C (A) 8

Applicable Standard IS 8130/2013, IS 7098 Part I/88, IS 5831/84, IS 3975/1999 etc. with latest up to date amendments

Approx. overall diameter of the cable in mm 30.5 ± 3.0

Minimum bending radius 12 times Overall diameter

Max. Tensile strength

(i) for Cables pulled with stocking (Newtons) 5 x D², D is the cable OD in mm

(ii) for Cables pulled with pulling eyes (N) 4575

Embossing POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE

Printing YEAR POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE
CABLE SIZE CABLE TYPE WITH SEQUENTIAL MARKING
at every one meter interval.

Standard Drum Length (Mtr.) 500 ± 5%

Non- Standard Drum Length (Mtr.) Maximum 5% of order quantity